



JAY R. SMITH MFG. CO.
 MEMBER OF MORRIS GROUP INTERNATIONAL
 POST OFFICE BOX 3237
 MONTGOMERY, ALABAMA 36109-0237 (USA)
 TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com




MEMBER OF:



LOCATION

14" WIDE 9879-903D-CB POWERDRAIN® INLINE CATCH BASIN w/INTEGRAL DUCTILE IRON RAIL



Note: See Back For Outlet Sizes And Flow Capacities

REGULARLY FURNISHED:

1/2 meter (1.64") Precast Polymer Concrete
 Catch Basin With An integral Ductile Iron Edge Rail.
 Total Capacity of 30 Gallons Supplied with Secured
 Ductile Iron Slotted Grate and Plastic Sediment Bucket.

VARIATIONS:

- Grate Specifications (See Back)
- 9879-UNV Universal 6"/8"/10" Closing/Inlet/Outlet End Cap
- 9879-FAT Foul Air Trap (4" only) -FAT
- 9879-GRT Grate Removal Tool

Note: This Trench Drain System is Designed for "On Grade Applications Only" as There are No Provisions for a Flashing Flange or Flashing Clamp

Note: This Catch Basin Comes Standard With Polymer Concrete Top, Powerlok Ductile Iron Grate, Plastic Bucket, And Plastic Base.



DRAWING NUMBER
9879-903D-CB

SIZE
A

SCALE:
NONE

DATE:
4-10-19

APPROVED BY:
PJ

CHECKED BY:
PJ

DRAWN BY:
MW

FIGURE NUMBER
9879-903D-CB

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA
 DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

| | | | | | | | |
|------|---------|--------------------|----|---------|------------------|----------------------|--------------------------------------|
| B | 1-16-2 | Revised Variations | TB | KV | WEIGHT POUNDS | VOLUME CUBIC FEET | FIGURE NUMBER 9879-903D-CB |
| A | 8-30-23 | Removed Function | HS | CL | | | |
| REV. | DATE | DESCRIPTION | BY | CKD. BY | | | |



JAY R. SMITH MFG. CO.
 MEMBER OF MORRIS GROUP INTERNATIONAL
 POST OFFICE BOX 2237
 MONTGOMERY, ALABAMA 36109-0237 (USA)
 TEL: 334-277-8520 FAX: 888-377-7818
 www.jrsmith.com



LOCATION

14" WIDE 9879-903D-CB POWERDRAIN® INLINE CATCH BASIN w/INTEGRAL DUCTILE IRON RAIL

**Extra Heavy Duty, EN 1433 Load
 Class E: 135,000 lbs - 2323 psi. For commercial solid tire forklift traffic patterns, forklifts and impacts from steel struts or metal wheels.**

* **9879-ADAG Powerlok ADA** - 1 3/8 x 7/16 longitudinal ductile iron slotted grate (56.00 sq in.)

**Extra Heavy Duty, EN 1433 Load
 Class F: 202,320 lbs - 4182 psi. For aircraft runways, docks, heavy fork trucks, and heavy wheel loads.**

* **9879-SLG Powerlok Slotted** - 3 13/16 x 7/16 ductile iron slotted grate (126.00 sq in.)

*Available With Powerlok Locking Devices Only

Outlet Flow Rates

| Outlet | Outlet Size | Invert Inches | Invert mm | GPM | CFS |
|--------|-------------|---------------|-----------|------|------|
| A | 4" round | 29.80 | 757 | 287 | 0.64 |
| B | 4" round | 36.29 | 922 | 319 | 0.71 |
| C | 4" round | 28.22 | 717 | 279 | 0.62 |
| D | 6" round | 36.29 | 922 | 707 | 1.57 |
| E | 4" round | 28.38 | 721 | 280 | 0.62 |
| F | 4" round | 34.88 | 886 | 312 | 0.70 |
| G | 6" round | 29.15 | 740 | 626 | 1.40 |
| H | 4" round | 28.59 | 726 | 281 | 0.63 |
| J | 6" round | 36.28 | 922 | 707 | 1.57 |
| K | 4" round | 35.72 | 907 | 316 | 0.70 |
| L | 6" round | 35.72 | 907 | 701 | 1.56 |
| M | 8" round | 36.28 | 922 | 1237 | 2.76 |
| N | 6" round | 34.78 | 883 | 690 | 1.54 |
| P | 4" round | 27.65 | 702 | 276 | 0.61 |
| Q | 4" round | 34.36 | 872 | 310 | 0.69 |

Note: These are the pipe flow rates at the specified outlet, NOT channel flow rates. Catch basin flow rates are without trash bucket - using trash bucket reduces flow.

DRAWING NUMBER
9879-903D-CB-BS

SIZE
A

SCALE:
NONE

DATE:
4-10-19

APPROVED BY:
PJ

CHECKED BY:
PJ

DRAWN BY:
MW

FIGURE NUMBER
9879-903D-CB-BS

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE



| | | | | | | | |
|------|--------|--------------------|----|---------|---------------|-------------------|------------------------|
| A | 1-16-2 | Revised Selections | TB | KV | WEIGHT POUNDS | VOLUME CUBIC FEET | FIGURE NUMBER |
| REV. | DATE | DESCRIPTION | BY | CKD. BY | | | 9879-903D-CB-BS |