



BOXER™

A lot of Water Fast, at the Right Temperature, When You Don't Have Time to Waste!



Meet Boxer™! Ideal for emergency drench shower and eyewash applications, Boxer™ delivers the knock-out punch by providing endless reliable tepid water with 3.0 to 30.0 gpm flow rates. Compliant with ANSI Z358.1.

800-447-4962 • www.chronomite.com

BOXER™

Chronomite ERB Series heaters are designed with multiple activations. Low activation is ideal for Emergency Safety Eyewash/Facewash combination with Drench Shower. The Standard activation is ideal for Commercial and Industrial tank heating. The High activation model is designed to work with Emergency Safety Drench Shower Equipment.

Features and Benefits:

- Digital microprocessor provides ultra quick response time, controlling hot water temperatures 120x per second. Eliminates concern of scalding and the need for mixing valves.
- Several models available with power up to 154 KW and flow ranges from 3 to 30 gpm.
- 99% energy efficient for water and energy savings.
- Rugged stainless steel construction.
- Can provide 84° tepid water to meet ANSI Z358.1.

CHRONOMITE - BOXER™ - 3 PHASE - LOW ACTIVATION

Dimensions:	26-3/4" x 21" x 7-1/2"
Weight:	76 LBS
Materials:	Rugged stainless steel housing Celcon plastic element assembly with Nichrome coils
Minimum Operating Flow Rate:	3.0 GPM
Minimum Operating Pressure:	25 PSI
Maximum Operating Pressure:	80 PSI
Maximum Pressure:	150 PSI
Maximum Operating Temperature:	160°F
Listing:	UL, UPC

GENERAL NOTES:

- The microprocessor adjusts the heater's power for variations in flow rates, inlet water temperature and pressure to assure the selected water temperature
- 240V models when operated at 220V will have approximately a 15% wattage decrease
- For EFD units - order ERB-L9 series option (F) with 84°F water

