

A171.8-UG-SO Series

BASE MODEL A171108-UG-SO

BARRIER FREE, SENSOR OPERATED,
WALL MOUNTED WATER COOLER

STANDARD FEATURES

- Rough-Ins Match Other Manufacturer's for Easy Replacement
- Lead-Free
- Child or Adult ADA Compliant (When Properly Installed)
- Apron and One-Piece Bottom Wrapper is Satin Finish Or Gray Powder Coat Finish
- Flexible, Low Flow, Anti-Rotation, Non-Squirt Bubbler
- 100-Mesh Inlet Strainer
- Hanging Bracket Provided
- 9 Volt Sensor Operation
- Chiller Includes Water Leak Detection Auto Shut-Off Valve

SUGGESTED SPECIFICATIONS

Model A171108F-SO is a self-contained, Sensor Operated Water Cooler that shall deliver a minimum of **8.0 GPH** (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90°F (32.2°C) ambient. Unit shall be activated by a front mounted 9 Volt Infrared Sensor. Bubbler shall deliver a 0.3 GPM flow, have an Anti-Microbial Flexible Guard with an integrally designed Non-Squirt feature and operate on a water pressure range of 20-105 PSIG. Basin shall be constructed from 304 Stainless Steel and have an integral Drain. Cabinet shall be either Galvanized or Galvannealed Steel with Gray Powder Coat Finish or Stainless Steel with Satin Finish. Cooling system shall use R-134a Refrigerant and be Capillary Tube controlled. Chiller shall include Factory installed Water Leak Detection Auto Shut-Off Valve. Unit shall be listed by Underwriters Laboratories for both the US and Canada and is to be compliant to ANSI/ASHRAE 18. Unit shall be certified to Public Law 111-380 (NO-LEAD) and NSF/ANSI/CAN 61. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.

Model Number	GPH*	Rated Watts	Full Load Amps	Approx. Shipping Weight
A171108S-UG-SO	8.0	335	4.1	56 lbs.

* GPH of 50°F water at 90°F ambient room temperature and 80°F inlet water temperature
Compressor motor operates on 115 Volt / 60 Hz single phase.

Complies with the following standards:



NSF/ANSI/CAN 61

ANSI/ASHRAE 18



Model A171108F-UG-SO Shown
PATENT# 10,100,933



MODEL:
(Must Specify)

"RATED FOR INDOOR USE ONLY"

FLEXIBLE BUBBLER

- A171108F-UG-SO Gray Finish (Standard - Shown)
- A171408F-UG-SO Satin Stainless Finish

STAINLESS STEEL BUBBLER

- A171108S-UG-SO Gray Finish
- A171408S-UG-SO Satin Stainless Finish

OPTIONS:

(Additional costs may apply.)

- LOGO Customer Specified Logo / Graphics
- 220V 220 Volt / 50 Hz or 60Hz Compressor

ACCESSORIES:

(Additional costs may apply. Accessory items are packaged separately.)

- WF3000 3000-Gallon PFAS Water Filter¹
NSF/ANSI, PFAS, Lead, Bacteria, Chlorine, Microplastics
- SK5 Cane Detection Skirt for Upper Unit¹
Skirt finish provided to match Model selected above
(P.N. A000G000-SK5 Gray, A0004000-SK5 Satin Stainless)

NOTES:

1- Refer to Supplemental Submittal Sheet for details.

Compatible Mounting Support Carrier

Jay R. Smith Mfg. Co. Figure # 0830 <https://www.JRSmith.com>

NSF/ANSI/CAN 61: Q ≤ 1

NSF/ANSI/CAN 61 Compliant including lower lead leaching criteria.


3000 Gallon PFAS Filter Certifications

Product Warranty



⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

A171.8-UG-SO Series

BASE MODEL A171108-UG-SO
BARRIER FREE, SENSOR OPERATED,
WALL MOUNTED WATER COOLER



- A. 3/8" O.D. SUPPLY INLET
- B. WASTE OUTLET FOR P-TRAP BY OTHERS FOR PROVIDED 1-1/4" O.D. TAILPIECE
- C. ELECTRICAL SERVICE ROUGH
- D. Ø3/8" HANGER BRACKET PUNCHING, 6 PLACES FOR ANCHORING HARDWARE BY OTHERS
- E. Ø1/4" PUNCHING, 2 PLACES FOR ANCHORING HARDWARE BY OTHERS
- F. DRINKING FOUNTAIN SENSOR
- G. REMOVABLE PLUG FOR BOTTLE FILLER (-BF11 OR -BF12 ONLY)
- H. 1-1/4" [32] O.D. TAILPIECE FOR P-TRAP BY OTHERS



GENERAL NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MM]
2. ALLOW 4 INCHES [102 MM] MINIMUM CLEARANCE PER SIDE FOR VENTILATION
- *3. DIMENSIONS SHOWN ARE FOR ADA ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES
4. STOP VALVE, P-TRAP, & ELECTRICAL OUTLET NOT SUPPLIED
5. IMPORTANT: COOLERS MUST BE ATTACHED TO WALL WITH APPROPRIATE ANCHOR SCREWS

IMPORTANT: Dimensions are shown for reference only. Refer to product Installation Manual for complete details prior to Rough-in.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

Model Number & Options _____	Quantity _____
Company _____	
Contact _____	Title _____
Signature (Approval for Manufacturing) _____	Date _____

All dimensions are subject to manufactures tolerance of plus or minus 1/4" nominal and subject to change without notice. Murdock[®] assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock[®] Mfg., Member of Morris Group International[®]. Please visit www.murdockmfg.com for most current specifications.