Option -MVCFV

Time-Trol Electronic Flush Valve

Provides an Acorn Time-Trol System for limiting frequency of flush valve operation through electronic control of a solenoid flush valve. Modular Valve Controller (MVC) includes 10 preset lockout intervals ranging from 1 second to 9 minutes easily adjustable with a dial selector knob. The pushbutton is vandal-resistant and requires less than 5 pounds to activate valve. MVC controller can be remotely located up to 100 feet from the fixture.

When specified, Acorn will provide a code approved Solenoid Flush Valve complete with Vandal Resistant Pushbutton, Vacuum Breaker, Tailpiece and Elbow. Not offered with -T Top Supply Toilets and Urinals unless provided with 2802 Series Flush Valve Cover (specified separately)

-W Wall Supply Toilets and Urinals with -MVCFV option are provided with an In-Wall Pneumatic Pushbutton and Concealed Solenoid Flush Valve. Pushbutton is suitable for ADA Compliance. *Typical Flush Valve models are provided from Sloan® ; Toilets: Regal 611-ES Series. Urinals: 195-ES Series.

Lav-Toilet Combination fixtures with -MVCFV option are provided with a Backsplash or Cabinet Mounted Pneumatic Pushbutton and concealed Solenoid Flush Valve. *Typical Flush Valve models are provided from Sloan® ; Front and Rear Access: Regal 603-ES Series.

Note: Provided as reference only. Refer to Manufacturer for complete data. Subject to change without notice.

Please visit **www.acorneng.com** for most current specifications.