

COMPACT FIXTURE SUPPORTS

WITH VERTICAL CENTER LINE FITTINGS FOR BLOWOUT WATER CLOSETS

DRAWING NUMBER **S0480**

SIZE **A**

SCALE: **NONE**

DATE: **10-27-69**

APPROVED BY: **RP**

CHECKED BY: **RP**

DRAWN BY: **RVB**

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

Fig. 0490 Side View

Fig. 0480 Side View

Front View

NOTE: When used with concealed flush valve, locate face plate behind supply pipe.

NOTE: Base support must be securely anchored to floor with four 1/2" (13) bolts provided by contractor.

NOTE: See reverse side for recommended setting of closet outlet connection and various modifications.

NOTE: Side inlet 1 1/2" (38) or 2" (51) N.P.T. or 2" (51) caulk (specify type and size)

WITH 2" (51) VENT

Fig. 0480 . . . CAULK

Fig. 0480B . . . THREAD

Fig. 0487 . . . CAULK Long Barrel

WITH 4" (100) VENT

Fig. 0490 . . . CAULK

Fig. 0490B . . . THREAD

Fig. 0497 . . . CAULK Long Barrel

Conforms to ASME A112.6.1M.

The water closet gasket regularly furnished is made of molded neoprene and designed to fit water closet outlet dimensions and configurations shown in ANSI Standard A112.19.2M-1995, Figure 13B. If gasket is not found to be compatible to fixture due to nonconformance of said fixture to ANSI A112.19.2M, then fixture manufacturer shall be consulted for a suitable gasket recommendation. Jay R. Smith assumes no liability for connections to fixtures which do not conform to these standards.

0480,0490

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

© DIMENSION - ADJUS-TO-WALL TYPE OUTLET CONNECTION

The Smith Adjus-to-Wall outlet connection provides adjustment at the face of the wall at the time the fixture is set; thus, compensating for wall construction variations. The © dimension is measured from the front of the face plate to the finished wall. To properly determine the length of nipple required, deduct 1" (25) from the © dimension. The Adjus-to-Wall coupling will provide 1/2" (13) horizontal adjustment in either direction with the coupling extended 5/16" (8) past face of the finished wall.

© dimension = 4" (100) (regularly furnished) consisting of nipple and Adjus-to-Wall coupling permitting adjustment from 3" (76) min. to 4" (100) max.

*ABS (Regularly Furnished) other lengths PVC.

NOTE: Dimensions shown in parentheses are in millimeters.

NIPPLE LENGTHS AVAILABLE

LENGTH	MIN	©	MAX
2 1/2 (64)	2 1/4 (57)	3 1/4 (83)	
*3 1/4 (83)	3 (76)	4 (100)	
*8 1/4 (210)	8 (205)	9 (230)	
10 (255)	9 3/4 (250)	10 3/4 (275)	
12 (305)	11 3/4 (300)	12 3/4 (325)	
15 (380)	14 3/4 (375)	15 3/4 (400)	
18 (455)	17 3/4 (450)	18 3/4 (475)	

NOTE: When nipple lengths between 3 1/4" (83) and 8 1/4" (210) are specified, the 8 1/4" (210) nipple will be supplied. Nipple must be cut to specified length by others.

REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 0480,0490