

DRAWING NUMBER S9760	<h1 style="margin: 0;">ROUND DECK PLUG</h1> <h2 style="margin: 0;">STAINLESS STEEL - CARBON STEEL</h2>
--------------------------------	--

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

Butt Weld Outlet
Schedule 40 Regularly Furnished

Fig. 9760C CAULK OUTLET
 Fig. 9760T THREADED OUTLET

A SIZE	B DIA		C	
	CAULK	BUTT WELD	CAULK	BUTT WELD
02(50)	4 1/2(115)	4 1/2(115)	3(76)	3(76)
03(75)	5 1/2(140)	4 1/2(115)	3(76)	3(76)
04(100)	7 1/2(190)	5 1/2(140)	▲3 1/4(83)	3 1/4(83)

▲ 3 1/8(79) for threaded outlet.

REGULARLY FURNISHED:
 CF8 (Equivalent to Type 304)
 Rough Finish Stainless Steel
 Body and Cover with Gasket.

VARIATIONS:
 Steel Spanner Wrench -SW
 BW Butt Weld Outlet - See Fig. No. 9762
 (Specify Schedule -S05, -S10, -S40 or -S80)

OPTIONAL MATERIALS:
 A-27 Carbon Steel -A27
 CF8M (Equivalent to Type 316)
 Stainless Steel -316
 Nickel Bronze Cover -NB

Design Pressures and Temperatures

1. With proper outlet connection, shall be watertight up to 10 ft. of water column (4.34 psig).
2. When exposed to effluent appropriate for drain material, the drain shall withstand effluent temperatures of 180 degrees F at ambient pressure.

NOTE: Dimensions shown in parentheses are in millimeters.

L	10-16-24	Revised Variations	HS	JT	WEIGHT	VOLUME	FIGURE NUMBER
K	8-28-23	Removed Function	HS	CL	POUNDS	CUBIC FEET	9760
J	5-23-17	Revised Table	TBW	CL			
H	8-12-16	Revised Variations	TBW	BW			
REV.	DATE	DESCRIPTION	BY	CKD. BY			

9760

FIGURE NUMBER

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov