

# PREMIUM, SUSTAINABLE CLEAN AGENT

for **SENSITIVE COMMERCIAL ENVIRONMENTS**

**ONCE EXCLUSIVE TO THE AEROSPACE INDUSTRY, THE HIGH PERFORMING HT-SERIES** for commercial settings can safely put out fires without damaging electronic equipment, specialized machinery, or other delicate materials. That also means that there is no clean-up or down time for your operations. Industries such as health care, clean manufacturing, data processing centers, and museums would all benefit from the HT Series. This fire extinguisher is also sensitive to the environment, meeting strict environmental regulations for Global Warming Potential and Ozone Depletion Potential. With knock down power and firefighting efficiency, the HT-Series using Halotron BrX agent features a steel cylinder, durable high-gloss polyester powder paint, and all-metal valve construction. Maximum visibility during discharge, a large stainless steel pull pin, and no electronic conductivity back to the user make this extinguisher extremely easy to use.

## KEY FEATURES AND BENEFITS:

- > Stored-pressure design for simple inspection
- > A low-GWP and very low-ODP product
- > No thermal or static shock
- > 12 year service life; non-rechargeable
- > Six-year manufacturer warranty
- > All-metal valve construction
- > Durable, high-gloss polyester powder-coat finish
- > Steel cylinder design
- > Flexible hose, all-metal hose for easy use
- > Leaves no residue
- > 7-day atmospheric lifespan
- > ABC Rating

## AGENT TYPE HALOTRON® BrX (2-BTP)

VALVE TYPE	Anodized Aluminum
DESIGN	Hose & Nozzle
UL & ULC RATING	2A:10B:C
CAPACITY (LBS.) / (KG)	12.5 / 5.67
FILLED WT. (LBS.) / (KG)	19.88 / 9.02
HEIGHT (IN.) / (MM)	20.25 / 514.3
WIDTH (IN.) / (MM)	8.5 / 215.9
DEPTH (IN.) / (MM)	5 / 127
DISCHARGE TIME (SEC.)	16
RANGE (INITIAL- FT. / M)	15-17 / 4.57-5.18
MINIMUM CONFINED SPACE REQUIREMENTS (FT3/ M3)	2,988 / 84.6
NOMINAL OPERATING PRESSURE	150 PSIG
INCLUDED BRACKET	Wall



**Designed and  
Manufactured  
in the USA**

MODEL NO. 3112



# 3115 HALOTRON I 3112 HALOTRON BRX

## SIMILARITIES & DIFFERENCES

### MODEL NO. 3115 HALOTRON I

- > 2A:10B:C rating
- > 15.5 lbs. of agent
- > 27.5 lbs. shipping weight
- > Discharge range 12-18 ft.
- > Min. confined space req. 2,170 cu. ft.
- > Operating pressure 125 PSI
- > Requires 6-year/12-year teardown
- > Rechargeable unit
- > Wall mount only
- > 6-year warranty
- > Low ODP and Low GWP
- > 3.5 years atmospheric lifespan



### MODEL NO. 3112 HALOTRON BRX

- > 2A:10B:C rating
- > 12.5 lbs. of agent
- > 19.8 lbs. shipping weight
- > Discharge range 15-17 ft.
- > Min. confined space req. 2,988 cu. ft.
- > Operating pressure 150 PSI
- > No 6-year/12-year teardown
- > Non-rechargeable unit
- > Will fit in standard cabinet
- > 6-year warranty
- > Low ODP and Low GWP
- > 7-day atmospheric lifespan



**STREET ADDRESS**  
15125 PROCTOR AVENUE  
CITY OF INDUSTRY, CA 91746

**MAILING ADDRESS**  
P.O. BOX 3527  
CITY OF INDUSTRY, CA 91744

**PHONE:** (800) 591-9683  
**E-MAIL:** INFO@POTTERROEMER.COM  
**WEBSITE:** POTTERROEMER.COM  
L1001702 | 0825