

murdock

OPTION -AP

Auto-Purge Function Controller



Murdock Manufacturing offers option -AP, the Auto-Purge Function Controller, as an add-on to BF12S and BF16S plug-in bottle fillers. These products feature an Auto-Purge Sensor which allows adjustment of Purge Cycle, Sensor Range and Lock-out functions. The -AP Sensor Function Remote Controller provides for adjustment of the Auto-Purge Timing Cycle, Infrared Sensor Detection Range and Activation Lock-out settings.

Features and benefits:

- Auto-Purge Settings: Factory set to activate the Bottle Filler for a 10 second purge, which occurs 24 hours after the last activation of the fixture.
- Adjustment of Auto-Purge: Timed intervals include an "OFF" Setting as well as 1 Hour, 2, 3, 6, 12, 24, 36, and 72 Hours. Adjustable Flow Duration when Auto-Purge occurs ranges from 1 to 60 seconds, in 1 second increments.
- Infra-red Sensor Range: Factory pre-set to suit fixture. Remote Controller allows Bottle Filler adjustment from 1/4" (6.4mm) to 2" (51mm) in 1/4" (6.4mm) increments. Faucet Sensor Range adjustments are possible from 2" (51mm) to 20" (508mm) in 1" (25mm) increments.
- Lock-Out Setting: Provides lock-out time to activate fixture for 1 - 30 minutes in 1 minute increments.



STREET ADDRESS
15125 PROCTOR AVENUE
CITY OF INDUSTRY, CA 91746

MAILING ADDRESS
P.O. BOX 3527
CITY OF INDUSTRY, CA 91744

PHONE: (626) 336-4561
E-MAIL: INFO@MURDOCKMFG.COM
WEBSITE: MURDOCKMFG.COM

L1001665 | 0225