



# Acorn-Sinks® Stainless Steel Drop-In Sink

Classroom Sink | Back and Left Faucet Ledge



<b>Base Model: CDLB-2220</b>
<b>SPECIFICATIONS</b>
Drop-In Style Installation
Single Bowl   Back and Left Faucet Ledge
O.D. Size: 22" x 19-1/2" (559mm x 495mm)
Bowl Size: 16" x 13-1/2" (406mm x 343mm)
Bowl Depth: 8" (203mm)
Type 304 Stainless Steel Material
18 Gauge (0.050") Thickness
#4 Polished Satin Finish
Drain Opening Size: 3-1/2" Dia. (89 mm)
Drain Location: Center
Mtg Hdwe up to 1-3/8" (35mm) Thick Counter



CDLB-2220-80-3

Fixture May Show Some Available Options



**Technical Details:** Acorn-Sinks® Self Rimming Drop-In Sink is seamless die-drawn construction of 18 gauge type 304, 18-8 stainless steel. Exposed surfaces are #4 satin finish with polished rim. Sink includes concealed "U" Channels with Hardware for mounting to underside of Countertop and Sound Deadening Insulation on Sink bottom exterior. Deck Punches are 1-1/2" (38mm) dia. and Slotted shown. Paper Template download available at [Acorn Website](#).

**Cut-Out Size:** 21-3/8" x 18-7/8" (543mm x 479mm) (1-1/2" (38mm) Corner Radius)

**Minimum Cabinet Size:** 27" (686mm) [Link to Info](#)

**Product Compliance:**

- ♦ ASME A112.19.3/CSA B45.4
- IAPMO® Certified for Conformance with:
- ♦ Uniform Plumbing Code® (UPC®)
- ♦ International Plumbing Code® (IPC®)
- ♦ National Plumbing Code of Canada® (NPC®)



CDLB-2220-80-3 Shown

**BASE MODEL NUMBER**

CDLB-2220-80 Classroom Sink, 8" Bowl

**BACK DECK (FAUCET) PUNCHING (Must Specify)**

Note: Includes Slotted Hole Left Ledge as Standard.

- 0 Blank: No Deck Punching, No Slotted Hole
- 1 Single Hole Centered
- 2 2 Holes on 4" Centers (4" Centerset)
- 3 3 Holes on 4" Centers (8" Centerset)

Optional Accessories are also available. Refer to [Supplemental Submittal](#) pages for details.

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**Important:** Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2023 Acorn Engineering Company

Selection Summary
Model No. & Option _____
Quantity _____

Approved for Manufacturing
Company _____ Title _____
Signature _____ Date _____

**CDLB-2220**

REV: 10/15/25




## REFERENCE


### Deck (Faucet) Punching Details

- Details shown are offered on the Stainless Steel Drop-In style sinks (SD and DD Series).
- Dimensions are from Sink centerline of either Single Bowl or Double Bowl (between basins).
- All Deck punching shown below includes 1-1/2" (38mm) diameter holes.
- Refer to individual Sink Submittal drawing for all other dimensional data.


#### **-1 Single Hole Centered**




**-2R Single Hole Centered with 2nd Hole 4" to Right**




**-3 Three Holes on 4" Centers (8" Centerset)**




**-4L Three Holes on 4" Centers with 4th Hole 4" to Left**



**-4R Three Holes on 4" Centers with 4th Hole 4" to Right**



**-2 Two Holes on 4" Centers (4" Centerset)**



**-5 Five Holes on 4" Centers**

⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Important:** Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2023 Acorn Engineering Company

SD-REF-1

Rev: 06/26/24




# Acorn-Sinks® Installation Instructions - Drop-In Sinks

Scan QR Code to view Installation Video.





## INSTALLATION STEPS

1. Position the sink upside down on the Countertop at desired location **[A]**.  
Using a Marking Tool, carefully trace the outer edge of the Sink and create outline.
2. Mark a line offset **5/16"** **TO THE INSIDE** of the outline of the Sink **[B]**. Detail corners with a **1-1/2" Radius**.  
**NOTE: Do not cut square corners.** The Cutaway area should be smaller than the original Sink outline.
3. Drill a pilot hole on the 4 corners of the **INSIDE** line.  
Using an appropriate Saw, cut out Sink opening (*Caution: Cutaway portion will fall off*).



4. Apply Silicone Caulk (by others) to topside of Countertop along the cutout **[C]**.
5. Carefully lower Sink into cutout as shown in Figure **[D]**.
6. Assemble the Clips and Screws as shown in Figure **[F]**.
7. From the underside, place a Clip in the center along each side and hand tighten to hold Sink in place. Fasten the remaining Clips along the edge and space them approximately 3" [76] from each end and equally along the front, back, and sides as shown in Figure **[E]** (Clip quantity differs with Sink size).
8. Check the seal between the Sink and Countertop. Lightly tighten Clips evenly until the Sink is snug against the Countertop **[G]**. Do not over tighten. Wipe away any excess Caulking.



Verify all applicable Plumbing Code requirements prior to installation. Mounting Faucet to Sink prior to installation may reduce time and labor.  
Note: For ADA Sink models: Compliance is subject to the interpretation and requirements of the Local Code Authority.

**TECHNICAL ASSISTANCE TOLL FREE TELEPHONE NUMBER: 1-800-743-8259**

**ACORN ENGINEERING COMPANY**

P.O. BOX 3527 • CITY OF INDUSTRY, CA 91744 U.S.A.  
TOLL FREE 800-488-8999

Drawing # 9000-M00-002 12/04/23 A