




# Acorn-Sinks® Stainless Steel Drop-In Sink

Double Bowl | Classroom Sink



<b>Base Model: CDDLB-3717</b>
<b>SPECIFICATIONS</b>
Drop-In Style Installation
Double Bowl, Classroom
O.D. Size: 37-1/4" x 17" (946mm x 432mm)
Bubbler Bowl: 9-1/4" x 12" x 3-1/2" Depth
Sink Bowl: 16" x 11-1/2" x 8" Depth
Type 304 Stainless Steel Material
18 Gauge (0.050") Thickness
#4 Polished Satin Finish
Drain Size: 2" Dia (51mm), 3-1/2" Dia (89 mm)
Drain Location: Centered
Mtg Hdwe up to 1-3/8" (35mm) Thick Counter



CDDLB-3717-80-3

Fixture May Show Some Available Options

**Technical Details:** Acorn-Sinks® Self Rimming Drop-In Sink is seamless die-drawn construction of 18 gauge type 304, 18-8 stainless steel. Exposed surfaces are #4 satin finish with polished rim. Sink includes concealed "U" Channels with Hardware for mounting to underside of Countertop and Sound Deadening Insulation on Sink bottom exterior. Deck Punches are 1-1/2" (38mm) dia. and Slotted shown. Paper Template download available at [Acorn Website](#).

**Cut-Out Size:** 36-5/8" x 16-3/8" (930mm x 416mm) (1-1/2" (38mm) Corner Radius)

**Minimum Cabinet Size:** 42" (1067mm) [Link to Info](#)

**Product Compliance:**

- ◆ ASME A112.19.3/CSA B45.4 IAPMO® Certified for Conformance with:
  - ◆ Uniform Plumbing Code® (UPC®)
  - ◆ International Plumbing Code® (IPC®)
  - ◆ National Plumbing Code of Canada® (NPC®)

Refer to [Supplemental Submittal](#) for optional Accessories.

**BASE MODEL NUMBER**

- CDDLB-3717-80 Classroom Sink, Left Bubbler, 8" Right Sink Bowl

**DECK (FAUCET) PUNCHING (Must Specify)**

- 0 Blank, No Deck Punching
- 1 Single Hole Centered
- 2R Single Hole Centered w/ 2nd Hole 4" to Right
- 2 2 Holes on 4" Centers (4" Centerset)
- 3 3 Holes on 4" Centers (8" Centerset)

Refer to Page 2 for Sink Dimensional Details

WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**Important:** Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2023 Acorn Engineering Company

Selection Summary
Model No. & Option _____
Quantity _____

Approved for Manufacturing
Company _____ Title _____
Signature _____ Date _____

**CDDLB-3717**

REV: 10/15/2025







# Acorn-Sinks® Deck (Faucet) Punching




## REFERENCE


### Deck (Faucet) Punching Details

- Details shown are offered on the Stainless Steel Drop-In style sinks (SD and DD Series).
- Dimensions are from Sink centerline of either Single Bowl or Double Bowl (between basins).
- All Deck punching shown below includes 1-1/2" (38mm) diameter holes.
- Refer to individual Sink Submittal drawing for all other dimensional data.



#### **-1 Single Hole Centered**




#### **-2R Single Hole Centered with 2nd Hole 4" to Right**




#### **-3 Three Holes on 4" Centers (8" Centerset)**



#### **-4L Three Holes on 4" Centers with 4th Hole 4" to Left**



#### **-4R Three Holes on 4" Centers with 4th Hole 4" to Right**



#### **-2 Two Holes on 4" Centers (4" Centerset)**

#### **-5 Five Holes on 4" Centers**

⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Important:** Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2023 Acorn Engineering Company

SD-REF-1

Rev: 06/26/24

Acorn Engineering Company • 15125 Proctor Avenue • P.O. Box 3527 • City of Industry, CA 91744-0527 U.S.A.  
Tel: (800) 488-8999 • (626) 336-4561 • [www.acorneng.com](http://www.acorneng.com) • E-mail: [info@acorneng.com](mailto:info@acorneng.com)




# Acorn-Sinks® Installation Instructions - Drop-In Sinks

Scan QR Code to view Installation Video.





## INSTALLATION STEPS

1. Position the sink upside down on the Countertop at desired location **[A]**.  
Using a Marking Tool, carefully trace the outer edge of the Sink and create outline.
2. Mark a line offset **5/16"** **TO THE INSIDE** of the outline of the Sink **[B]**. Detail corners with a **1-1/2" Radius**.  
**NOTE: Do not cut square corners.** The Cutaway area should be smaller than the original Sink outline.
3. Drill a pilot hole on the 4 corners of the **INSIDE** line.  
Using an appropriate Saw, cut out Sink opening (*Caution: Cutaway portion will fall off*).



4. Apply Silicone Caulk (by others) to topside of Countertop along the cutout **[C]**.
5. Carefully lower Sink into cutout as shown in Figure **[D]**.
6. Assemble the Clips and Screws as shown in Figure **[F]**.
7. From the underside, place a Clip in the center along each side and hand tighten to hold Sink in place. Fasten the remaining Clips along the edge and space them approximately 3" [76] from each end and equally along the front, back, and sides as shown in Figure **[E]** (Clip quantity differs with Sink size).
8. Check the seal between the Sink and Countertop. Lightly tighten Clips evenly until the Sink is snug against the Countertop **[G]**. Do not over tighten. Wipe away any excess Caulking.



Verify all applicable Plumbing Code requirements prior to installation. Mounting Faucet to Sink prior to installation may reduce time and labor.  
Note: For ADA Sink models: Compliance is subject to the interpretation and requirements of the Local Code Authority.

**TECHNICAL ASSISTANCE TOLL FREE TELEPHONE NUMBER: 1-800-743-8259**

**ACORN ENGINEERING COMPANY**

P.O. BOX 3527 • CITY OF INDUSTRY, CA 91744 U.S.A.  
TOLL FREE 800-488-8999

Drawing # 9000-M00-002 12/04/23 A