



- 1- ADJUST SPRAY PATTERN BY ROTATING THE ADJUSTABLE INSERT, ITEM #4, WITH A 1/8" HEX WRENCH (ACCESS THRU THE SHOWER NOZZLE ORIFICE).
- 2- TO REMOVE SHOWER NOZZLE, FIRST UNSCREW ITEM #8 THEN REMOVE ITEM #3 SHOWER NOZZLE USING ITEM #10 WRENCH.
- 3- SHOWER HEAD FLOW CONTROL (2 1/2 GPM) IS LOCATED IN THE VALVE BODY.

1	1244-002-001	SPACE-SAVER SHOWER HEAD -ASSY	6	1244-002-199	PENAL SPACE-SAVER SHOWER HEAD
2	1241-001-001	SHOWER NOZZLE -ASSY	7	1891-007-000	MALE 3/8" FLARE x 1/4" NPT FITTING
3	1241-001-199	PENAL SHOWER NOZZLE	8	0186-002-000	#10-32 x 3/8" SET SCREW CONE PT.
4	1188-000-199	ADJUSTABLE INSERT	9	0126-504-000	1/4"-20 x 3/8" PHIL PAN HD SCREW
5	0421-019-000	GASKET	10	0356-000-001	PENAL SHOWER HD WRENCH
ITEM	PART NUMBER	DESCRIPTION	ITEM	PART NUMBER	DESCRIPTION



ACORN ENGINEERING COMPANY
 P.O. BOX 3527 INDUSTRY, CA. 91744
 (626) 336-4561 FAX (626) 961-2200

TITLE		
PENAL-WARE SHOWER HEAD (CAT #1756 SPACE-SAVER)		
MANUFACTURE DATE	DATE ISSUED	DRAWING NUMBER
NOVEMBER 1982	09/01/89	
TO PRESENT	DATE REVISED	9970-001-003
	09/22/09	