



## Option -CSH-WSA



Model -CSH-WSA Shown



### Ligature Resistant WaterSense® Labeled Conical Showerhead

Showerhead is certified and labeled for WaterSense® Specifications for Showerheads Version 1.1 and complies with requirements listed under ASME A112.18.1 / CSAB125.1. IAPMO cUPC. [Link To Certification](#)

**The ligature resistant, high efficiency Showerhead includes** a Removable Vandal Resistant, Stainless Steel, Non-Aerated, Multi-Stream, Spray Nozzle which is fitted with an internal 1.5 GPM (5.7LPM) Flow Restrictor. The Spray Nozzle is vandal resistant and requires a Spanner Wrench (provided) for removal.

**The Conical shape of the Showerhead** prevents it from being used as a point of ligature and provides a 30 degree fixed spray angle. The Conical Body and Spray Insert are machined from type 303 stainless steel and polished to a mirror finish.

**Model -CSH-WSA Showerhead** is intended for mounting on our Stainless Steel Shower Panels and is bolted to Panel from the rear with (2) concealed 1/4"-20 UNC Stainless Steel Screws.

**Note:** This showerhead includes vandal resistant features and WaterSense® certification and is serviceable from the user side of the shower fixture using a specialized tool. Prior evaluation is recommended before using the showerhead in high security applications.

Please visit [www.acorneng.com](http://www.acorneng.com) for most current specifications.

⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

