

B	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: PLUMBING AND DRAINAGE INSTITUTE				LOCATION				
	Snap-N-Go!® FINISHED FLOOR CLEANOUTS WITH TWIS-TO-FLOOR® ADJUSTABLE TOPS ROUND NICKEL BRONZE TOP WITH ROUGH ADJUSTMENT SLEEVE								
DRAWING NUMBER s4020-ras series	SIZE A	SCALE: NONE	DATE: 04-16-2024	APPROVED BY: CL	CHECKED BY: CL	DRAWN BY: KK	WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE		
Adjustable Top with "CO" Cast in Secured Cover Rough Adjustment Sleeve (RAS) with Protective Cover Flashing Clamp (When Specified) Flashing Flange (When Specified) 3 1/2 (89) Plug Size 5 3/4 (145) DIA Min. 7/8 (22) Max. 2 1/4 (57) Min. 2 11/16 (68) Max. 4 1/8 (105) 2 1/4 (57) 4 (102) 2 3/16 (56) A 9 (230) Dia. TWIS-TO-FLOOR® ADJUSTMENT NO-HUB OUTLET A (Pipe Size) = 02(50), 03(75), 04(100), or 05(125) ☐ Fig. 4020RAS-SGasket Seal - ABS Plug ☐ Fig. 4021RAS-SGasket Seal - Bronze Plug ☐ Fig. 4023RAS-STaper Thread - Bronze Plug ☐ Fig. 4024RAS-STaper Thread - ABS Plug REGULARLY FURNISHED: Cast Iron Cleanout Ferrule with Round Adjustable Scoriated Secured Nickel Bronze Top with Rough Adjustment Sleeve. Closure Plug Type as Indicated By Figure Number Selected. VARIATIONS: ☐ Flashing Flange -F ☐ Flange with Flashing Clamp -F-C OPTIONAL MATERIALS: ☐ Polished Bronze Top -PB U.S. PATENT 10,683,654 CANADIAN PATENT 3,021,711									
FIGURE NUMBER	4020-RAS SERIES	B	3-11-25	Revised DWG	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
REV.	DATE	DESCRIPTION	BY	CKD. BY	4020-RAS SERIES				