



**NOTE:**  
USE OF TEFLON TAPE ON ALL THREADED CONNECTIONS IS RECOMMENDED

**IMPORTANT!** AFTER INSTALLATION, ALL JOINTS REQUIRE SECURITY SEALANT BY INSTALLER TO ELIMINATE GAPS BETWEEN WALL AND FIXTURE.

**INSTALLATION INSTRUCTIONS:**

- A- PRIOR TO MAKING UP CONNECTIONS TO VALVE ASSEMBLY, FLUSH SUPPLY LINES THOROUGHLY.
- B- MAKE UP SHOWER RISER CONNECTION FROM VALVE TO 1/2" NPT MALE SHOWERHEAD INLET (1).
- C- FIT ESCUTCHEON GASKET (2) INTO SHOWERHEAD ESCUTCHEON (3) AND SECURE BY THREADING SPRAYHEAD ADAPTER (5) INTO SHOWERHEAD INLET.
- D- THREAD ANTI ROTATION SPRING PIN (4) INTO SHOWERHEAD ESCUTCHEON (3) POSITION AS SHOWN.
- E- INSTALL CONICAL SHOWERHEAD (7) ONTO SHOWERHEAD ESCUTCHEON (5) AND SECURE USING SET SCREW (6) POSITION AS SHOWN.

WHITEHALL MANUFACTURING  
P.O. BOX 3527 Industry, CA 91744  
15125 Proctor Ave Industry, CA 91746  
(626) 968-6681 FAX (626) 855-4862

TITLE <b>WHD-SHD-W, LIGATURE RESISTANT WALL MOUNTED SHOWER HEAD</b>		
MANUFACTURE DATE <b>JUNE 2021 TO PRESENT</b>	DATE ISSUED <b>06/17/21</b>	DRAWING NUMBER <b>9918-304-001</b>
	DATE REVISED <b>01/18/23</b>	