

F

SMITH® JAY R. SMITH MFG. CO.®
 MEMBER OF MORRIS GROUP INTERNATIONAL
 POST OFFICE BOX 3237
 MONTGOMERY, ALABAMA 36109-0237 (USA)
 TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com



MEMBER OF:

LOCATION

DRAWING NUMBER
S9646-ST/9646-ST-S-BS

SIZE
A

SCALE:
NONE

DATE:
1-15-18

APPROVED BY:
CEL

CHECKED BY:
CL


DRAWN BY:
TBW

9646 -ST/9646 -ST-S-BS

FIGURE NUMBER

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA
 DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE



GENERAL PURPOSE FLOOR CLEANOUT 8"(150) ROUND & 8 1/2"(165) SQUARE




USDA ACCEPTED



ASME A112.36.2M &
 CSA B79
 Certified Heavy Duty
 Load Rating



Secured Cover



A (Pipe Size) = 06(150)

- | | |
|--|--|
| ROUND TOP | SQUARE TOP |
| Fig. <input type="checkbox"/> 9646BW-ST BUTTWELD OUTLET | <input type="checkbox"/> 9646BW -ST-S▲ |
| Fig. <input type="checkbox"/> 9646T-ST THREADED OUTLET..... | <input type="checkbox"/> 9646T -ST-S |
| Fig. <input type="checkbox"/> 9646Y-ST NO-HUB OUTLET | <input type="checkbox"/> 9646Y -ST-S |

▲Schedule 40 Regularly Furnished

REGULARLY FURNISHED:

14 Gauge Type 304 Stainless Steel Body with Secured Smooth Cover and HDPE Closure Plug. Body Rim and Cover Polished to a No. 4 Finish.

VARIATIONS:

- Anchor Flange -F
- Flange & Flashing Clamp -FC
- Type 304 Stainless Steel Closure Plug -XPSS
- USDA Compliant

OPTIONAL MATERIALS:

- Type 316 Stainless Steel -316

SUBJECT TO MANUFACTURING TOLERANCE AND CHANGE WITHOUT NOTICE.

NOTE: Dimensions shown in parentheses are in millimeters.

F	8-18-23	Removed Function	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
D	12-13-21	Added ASME and CSA numbers	KK	CL			
D	11-14-21	Rev. Certified Duty Load Rating	KK	CL	9646 -ST/9646 -ST-S-BS		
C	12-7-18	Revised Text, Figure Number	TBW	CL			
REV.	DATE	DESCRIPTION	BY	CKD. BY			



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov