

## GR Series

**MODEL GRM45**  
BARRIER FREE, BI-LEVEL  
PEDESTAL MOUNTED  
DRINKING FOUNTAIN

### STANDARD FEATURES

- Resistant to sunlight, heat, moisture and wear
- 18 Gauge, Type 304 stainless steel Bowl
- Heavy Gauge, Type 304 stainless steel, corrosion and scratch resistant finish
- Polished Stainless Steel, Anti-Rotation Non-Squirt Bubbler
- 100-Mesh Inlet Strainer
- Access Door, heavy duty stainless steel, vandal resistant
- Vandal resistant stainless steel Bottom Plate

### SUGGESTED SPECIFICATIONS

Model GRM45 is a Barrier Free Pedestal Mounted, Vandal Resistant, Bi-Level Round Drinking Fountain made from 18 gauge, Type 304 stainless steel Bowls mounted into a green powder coated heavy gauge, Type 304 stainless steel Pedestal. Unit shall be activated by front mounted self-closing Buttons, by using less than 5 pounds of force, which activates internally mounted Valves with adjustable stream regulators controlling the water flow. Bubblers shall be polished stainless steel with non-squirt features and operate on water pressure range of 20 - 105 PSIG. Unit shall be certified to Public Law 111-380 (NO-LEAD) and NSF/ANSI/CAN 61. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.

**Options Notes:**

<sup>1</sup> See separate option sheet.

<sup>2</sup> This option is not available freeze-resistant.



### MODEL:

(Must Specify)

- GRM44 Satin stainless finish
- GRM45 Green powder-coated (Shown)
- GRM46 Red powder-coated
- GRM47 Blue powder-coated

Custom color finishes available upon request

### OPTIONS

(additional costs may be incurred)

- CH30 Child height, 30" Bubbler height
- FRU2 Freeze resistant, 2 Valves <sup>1</sup>
- FRU3 Freeze resistant, 3 Valves <sup>1</sup>
- FRU4 Freeze resistant, 4 Valves <sup>1</sup>
- FS Foot Shower
- HB1 Hose Bibb, compression, w/ hose threaded outlet/VB <sup>1 2</sup>
- HB3 Hose Bibb, loose key, vandal resistant, locked door with hose threaded outlet/VB <sup>1 2</sup>
- IAP In-ground Anchor Plate
- IGM In-ground 14" Mounting Adapter
- JF1 Jug Filler, Spigot, self-closing Valve with Plain End <sup>1 2</sup>
- JF2 Jug Filler, Pushbutton, self-closing Valve w/ Plain end <sup>1</sup>
- JFFR1 Jug Filler, Pushbutton, Freeze Resistant, self-closing Valve <sup>1</sup>
- LSR Bowl with Leaf and Debris Strainer <sup>1</sup>
- NP2 Non-Pollutable, Freeze Resistant, 2 Valves
- NP3 Non-Pollutable, Freeze Resistant, 3 Valves
- PF Pet Fountain Receptor <sup>1</sup>

Complies with the following standards:



Federal Public Law 111-380 (No Lead)



Recyclable Product



Water Conserving Product

**Product Warranty**


⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**IMPORTANT: INSTALLATION AND SITE PREP FOR FREEZE RESISTANT OPTIONS "-FRU, -NP" WILL DIFFER FROM STANDARD. REFER TO FRU FREEZE RESISTANT INSTALLATION DETAILS.**


**GR Series**

**MODEL GRM45**


**BARRIER FREE, BI-LEVEL  
PEDESTAL MOUNTED  
DRINKING FOUNTAIN**



\* Valve specifications:  
Minimum/Maximum Pressure  
30 to 100 PSI.



**OPTIONAL -PF PET FOUNTAIN  
DETAIL**



**General Notes:**

1. All dimensions are in inches [mm].
- \*2. Standard adult ADA height model shown. Optional -CH30 child ADA height model available.
3. Stop Valve not provided.

**SELECTION SUMMARY  
& APPROVAL FOR  
MANUFACTURING**

Model Number & Options \_\_\_\_\_ Quantity \_\_\_\_\_

Company \_\_\_\_\_

Contact \_\_\_\_\_ Title \_\_\_\_\_

Signature (Approval for Manufacturing) \_\_\_\_\_ Date \_\_\_\_\_

*All dimensions are subject to manufactures tolerance of plus or minus 1/4" nominal and subject to change without notice. Murdock<sup>®</sup> assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock<sup>®</sup> Mfg., Member of Morris Group International<sup>®</sup>. Please visit [www.murdockmfg.com](http://www.murdockmfg.com) for most current specifications.*