

**A152-FG Series Barrier Free, Bi-Level, 14-Gauge Wall Mounted  
Drinking Fountain and 32" Trim Panel**



**A152400S-FG**

A152400F-FG / A152400S-FG & A152400F-FG-RBL / A152400S-FG-RBL  
**TECHNICAL ASSISTANCE TOLL FREE TELEPHONE NUMBER:**

**1.800.743.8259**

Technical Assistance E-Mail: [Fieldservice@acorneng.com](mailto:Fieldservice@acorneng.com)

**NOTES TO INSTALLER:**

1. Please leave this documentation with the owner of the fixture when finished.
2. Please read this entire booklet before beginning the installation.
3. Check your installation for compliance with plumbing, electrical and other applicable codes.

For current Warranty click hyperlink [Product Warranty](#) or visit: [www.murdockmfg.com/terms-and-warranty](http://www.murdockmfg.com/terms-and-warranty)

Murdock® assumes no responsibility for use of void or suspended data. © Copyright Murdock, City of Industry, CA Member of Morris Group International®. Please visit [www.murdockmfg.com](http://www.murdockmfg.com) for most current specifications.

**COMPLIES WITH  
STANDARDS**



Federal  
Public Law  
111-380  
(No Lead)



**NSF/ANSI/CAN 61**

Member of  
  
MORRIS GROUP  
INTERNATIONAL

**murdock**<sup>®</sup>  
SINCE 1853


15125 Proctor Ave.  
City of Industry, CA  
91746 U.S.A.  
Phone 800-453-7465  
626-333-2543  
[www.murdockmfg.com](http://www.murdockmfg.com)

**ROUGHING-IN AND DIMENSIONAL DRAWING**

Prior to roughing in, consult with local, state, and federal codes for proper mounting height.

**A152400S-VR Wall Mounted Drinking Fountain**

**NOTE:**  
Standard Bi-Level shown. -RBL Reverse Bi-Level, opposite




**GENERAL NOTES:**

1. ALL DIMENSIONS ARE IN INCHES (MM).
- \*2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES.

**NOTES:** Dimensions shown for Adult ADA compliant installation. For Child ADA compliant parallel approach installation, decrease height of installation by 3 inches. Provide clear floor space as required. Adjust vertical dimensions indicated with (\*) as required to comply with federal, state, and local codes.

**A152400S-FG Wall Mounted Drinking Fountain Inlet & Outlet Rough-Ins**




- ① SUPPLIED WALL MOUNTING PLATE
- ② 1-1/4" OD WASTE OUTLET
- ③ 3/8" NCT SUPPLY INLET

**NOTES:**

1. ALL DIMENSIONS ARE IN INCHES (MM).
- \*2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES.
3. STANDARD BI-LEVEL ROUGH-INS SHOWN. FOR -RBL REVERSE BI-LEVEL, MOUNTING FRAME ROUGH-INS OPPOSITE.



**ASSEMBLY:**



- A- REFER TO PAGE (4) TO INSTALL PROVIDED WALL MOUNTING PLATE (1).
- B- ROUGH-IN WASTE OUTLETS AT DIMENSIONS SHOWN PAGE (3) FOR 1-1/4" OUTER DIAMETER PLAIN END P-TRAPS (2).
- C- ROUGH-IN WATER SUPPLIES AT DIMENSIONS SHOWN ON PAGE (3). THE 1/4" NOMINAL (3/8" O.D.) x 4" LONG COPPER TUBES (3) CONNECTED TO "Y" STRAINER (4).
- D- CAREFULLY REMOVE FIXTURES (5) AND COMPONENTS FROM THE PACKAGING PREVENTING SCRATCHING AND DAMAGE.
- E- REMOVE SCREWS (6) TO REMOVE BOTTOM ACCESS PANEL (7) ASIDE WHERE THEY WILL NOT GET DAMAGED.
- F- SLIDE SPACERS (8), BACK PLATE (9) AND FIXTURES (5) OVER STUDS (10) FROM MOUNTING PLATE (1) & SECURE WITH NUTS AND WASHERS (11).
- G- ASSEMBLE P-TRAPS (2) TO DRAIN ADAPTERS (12). ASSEMBLE TO UNITS BY SECURING WITH NUT (13). MAKE-UP 1-1/4" O.D. WASTE CONNECTIONS.
- H- FLUSH WATER SUPPLIES OF ALL DEBRIS PRIOR TO CONNECTING TO FIXTURE.
- I- CONNECT WATER SUPPLIES TO 1/4" NOMINAL COPPER COPPER TUBE (3). STRAIGHT SUPPLY STOPS RECOMMENDED.
- J- TEST OPERATION OF BUBBLERS BY DEPRESSING BUTTONS (14). SEE DETAIL ABOVE TO ADJUST FLOW RATE AS REQUIRED. CHECK ALL CONNECTIONS AND WASTE PIPING FOR LEAKS. CORRECT IF PRESENT.
- K- RE-INSTALL BOTTOM ACCESS PANEL (7) AND SECURE WITH SCREWS (6).

**IMPORTANT:**

1. Water Supply Service Stop Valve and Water Connections to be supplied by others in accordance with local codes.
2. Waste is 1-1/4" Outer Diameter. Drinking Fountain water inlet is 3/8" Outer Diameter copper tube. Water line by others.
3. If required, a 120VAC, 60Hz, 3A (MAX) GFCI protected, electrical receptacle, by others.
4. Completely flush supply lines of all foreign debris before connecting to fixture. Optional Water Filter (WF1), is available should any problems with taste, odor, color, or sediment arise from the water supply.
5. All burrs must be removed from outside of cut tubes before inserting into strainer or other components.
6. *Per UPC 609.10-All building water supply systems in which quick acting valves are installed shall be provided with devices to absorb the hammer caused by high pressure resulting from the quick closing of the valve. These pressure-absorbing devices shall be approved mechanical devices. Water pressure-absorbing devices shall be installed as close as possible to the quick closing valve.*

**PRIOR TO INSTALLATION:**

1. Read all installation instructions carefully, before proceeding.
2. Carefully remove all fixture components from packaging, preventing scratching or damage. Inspect fixture and all parts from damages and all parts that are bolted on.
3. Provide mounting surface, adequate to support the fixture and loads on the fixture.
4. Provide rough-ins as shown on the roughing-in and dimensional drawing, including water supply, and drain pipe. (See rough-in details)
5. Completely flush water supply lines of all foreign debris, before connecting to the fixture.

**DRINKING FOUNTAIN INSTALLATION:**

1. Insert mounting frame into the rough-in block out and secure using appropriate mounting hardware (Provided by Others).
2. Install the four threaded studs into the Wall Mounting Frame.
3. Slide Spacers onto provided 5/16" threaded rod then install Trim panel over rods.
4. Remove the drinking fountain top by taking out the drain screw and lifting at the front while pulling forward. Disconnect bubbler tube. Set top aside in a safe place where it will not be damaged. Place the screw in a secure location where it will not be lost.
5. Slide Fixture over studs and secure with nuts and washers.
6. Assemble P-trap to drain adapter and then assemble to unit with Phillips head screws.
7. Make-up 1-1/4" outer diameter waste connection.
8. After thoroughly flushing the 3/8" O.D. supply line, connect to push-in fitting or "Y" Strainer.
9. Place drain gasket on drain adapter. Reconnect bubbler tube. Reassemble top to unit by engaging back clip and securing with screw.

**DRINKING FOUNTAIN START UP:**


1. Before connecting power supply (if required), but after thoroughly flushing the supply line, turn on building water supply and check all connections for leaks.
2. Air within the drinking fountain system or the structure supply piping will cause an irregular bubbler outlet stream until purged out by incoming water. Covering the bubbler with a clean cup (or similar object) is recommended when first activating drinking fountain to prevent excessive splashing. Depress front push pad until steady water stream is achieved.
3. If water flow requires adjustment, for the A152-FG, insert a slotted narrow blade screwdriver in the hole centered of the Pushbutton to the flow regulator. Turning clockwise will increase flow and turning counterclockwise will decrease flow. See page 5 for details.
4. Recheck all water connections with water flowing through system.

### **PUSH-IN FITTING INSTALLATION**

NOTE: FITTINGS AND TUBE SHOULD BE KEPT CLEAN, BAGGED AND UNDAMAGED PRIOR TO INSTALLATION.


#### **TO CUT TUBE:**

Cut to fit length of 1/4" PE tubing and remove any burrs or sharp edges. Ensure that the outside diameter is free from score marks. Tube ends should be square.




#### **INSERTING THE TUBE:**

1. Firmly and fully insert the tubing end into the push-in fitting up to the tube stop located approximately 1/2" deep.




2. Pull on the fitted tubing to ensure it is secure. Tube should not come free from the fitting. Water test the connection assembly prior to leaving the site to ensure there are no leaks.



#### **DISCONNECTING THE TUBE:**

To disconnect the tube from the fitting ensure that the water line is depressurized. Push collet square towards the push-in fitting body and hold. While holding the collet in, pull on the PE tubing to remove from the push-in fitting.



## Trouble Shooting:

**IMPORTANT: BEFORE MAKING ANY OF THE REPAIRS LISTED, MAKE SURE THE WATER SUPPLY VALVE IS SHUT OFF.**

### TROUBLE SHOOTING:

#### **1. ADJUSTMENTS:**

- a. Cartridge – The water flow can be adjusted using a slotted narrow blade screwdriver and turning clockwise to increase flow and counterclockwise to decrease flow.
- b. Cold Water Thermostat – The water temperature can be adjusted using a slotted screwdriver and turning clockwise to make colder and counterclockwise to make warmer.
- c. Bubbler Stream - Bubbler can be rotated slightly to direct the stream backwards or forwards. Adjust the stream to minimize splashing. Splashing may occur from bubbler stream if the unit is not level. Shim lower mounting point, if necessary, to level chiller.

#### **2. RESTRICTED OR NO WATER FLOW:**

- a. Ensure water supply service stop valve is fully open.
- b. Verify minimum 20 psig supply line flow pressure.
- c. Check for twists or kinks in outlet tubing.
- d. Check the water inlet “Y” strainer. Sediment from the main supply can get trapped in the screen along with installation materials such as pipe dope and flux. The screen should be cleaned and checked on a regular basis and replace if needed.
- e. The cartridge valve located in the water control assembly or bubbler can also become clogged with foreign material. The cartridge valve can only be replaced and not repaired.
- f. Check flow adjustment. See start up note #3.
- g. Flow control in solenoid valve outlet elbow clogged remove & clean.
- h. No power to transformer connections, loose or wires cut.

#### **3. WATER DRIPS OR WILL NOT SHUT OFF:**

- a. Open fixture. Loosen nuts holding valve bracket assembly to bottom of fixture but, do not remove. Move complete valve bracket assembly further back from the front push pad and tighten to lock in place.
- b. Replace valve cartridge.

## Cleaning & Maintenance Guide:

### **STRAINER MAINTENANCE**

1. Periodically remove the bottom access panel remove and inspect inline “Y” strainer.


**For Powder coated units:** Units should be cleaned using a mild soap solution with a sponge or cotton cloth. Wipe down surfaces then rinse with clean water.

### **For Stainless steel units:**

1. To Remove water spots or rust spots, stainless steel cleaner/polish on a cloth is recommended.
2. If there are stubborn spots or if you wish to treat a scratch, synthetic abrasive general purpose pads such as scotch brite are recommended.
3. Stainless steel should be kept clean at all times. If a coating of stainless steel cleaner/polish is maintained, stainless steel surfaces will retain their new, clean, polished appearance indefinitely.

**DRINKING FOUNTAIN PARTS BREAKDOWN DRAWING**

**Shown is the 18" long unit, however the parts are the same for the 14" long unit.**



ITEM #	PART NUMBER	DESCRIPTION	ITEM #	PART NUMBER	DESCRIPTION
1	0112-012-000	#10-32 x 1/2" Hex C/R BTN HD Screw	7A	7000-012-001	Stainless Steel Bubbler Assembly
2	7000-015-000	1-1/4" OD P-Trap	7B	7000-099-002	Flexible Gray Bubbler Assembly
3	7000-021-002	"Y" Strainer Assem., 3/8" O.D. x 1/4" O.D.	8	7000-068-001	Retaining Ring & Button Assembly
4	7000-005-199	Drain Adapter	9	7000-060-000	Valve Cartridge
5	7000-006-000	Flat Drain Adapter Gasket	10	7000-065-001	Recessed Pushbutton Valve Assembly
6	0152-010-000	#10-32 x 1" Hex Flat Head C/R Screw	11	7003-093-001	Flow Restricto - Low Flow Bubbler Only

Repairs must be made with Murdock Manufacturing parts only. Please order through your local representative or distributor. The phone number to locate your local representative is 1.800.591.9360.