



Click on or tap the product image to access the complete submittal.



#### DRY WALL ELMDOR DW SERIES

Dry Wall Access Doors, size verified in field. Access door and frame shall be fabricated from 16 gage, galvannealed steel with a white prime coat finish. The door shall have rounded safety corners and a concealed pivoting rod hinge. Frame shall be one piece construction with no miters or welds on the face. Latch shall be screwdriver operated. Finish shall be a white prime coat suitable for painting.



#### FIRE RATED WALL ELMDOR FR SERIES

Fire Rated Access Doors, size verified in field. Access door and frame shall be fabricated from 16 gage, galvannealed steel with a white prime coat finish. Hinge shall be concealed type. Door shall have a heavy duty spring to provide positive latching when closed and an interior latch release slide enabling door to be opened from the inside. Exterior latch shall be recessed and operated using ring attached to the sliding bolt. Finish shall be a white prime coat suitable for painting. Fire Rated by Underwriters Laboratories Inc., for 1-1/2 hours, "B" Label, ANSI-UL 10B standard, and CAN/ULC S104 for 2 hours in walls. Door has a heavy duty spring closure to assure positive latching when panel closes. **This door is for wall installation only.**



#### FIRE RATED CEILING & WALL ELMDOR FRC SERIES

Fire Rated Ceiling Access Doors (specify model number and options). Access door frame shall be fabricated from 16 gage galvannealed steel with a white prime coat finish and provided with masonry anchors and bolt holes. Access door panel shall be fabricated from 20 gage, galvannealed steel with a white prime coat finish. Door shall be filled with 2" thick, fire rated insulation, and be welded pan type. Access door shall have automatic closure, be self-latching and contain interior latch release. Exterior latching shall be recessed and universal self-latching bolt, operated by either a knurled knob or flush key. Finish shall be a white prime coat suitable for painting. Underwriters Laboratories for 1-1/2 hours, "B" label in walls, Warnock Hersey for 3 hours in ceilings and 2 hours in walls, CAN/ULC S104 for 2 hours in walls.



WWW.ELMDOR.COM  
(626)968-8699

MEMBER OF

MORRIS GROUP  
INTERNATIONAL®  
L1001510DIG  
1121