



Why Chronomite® Electric Water Heaters?

Committed to quality products designed and adapted to work in our ever-changing plumbing market

1. The CM and CMI Series' low-flow activation of 0.2GPM works with all low-flow faucets.
2. Field-Adjustable Temperature switch.
3. CMI Series has built in TMV Heater to meet ASSE 1070 CODE.
4. Preset temperatures for safety applications -- no mixing valve required.
5. Flow switch prevents dry fire.
6. Invizible® accessory option-conceals your heater and disconnect switch in a vandal-resistant, easy access box.
7. Products designed for under sink installs, booster units, emergency showers, mop sinks and complete bathrooms.

Click on or tap the product image to access the complete submittal.

**THE R SERIES Invizible-Water-Heater™ PROVIDES
CONTINUOUS TEPID WATER
TO AN EYE/FACE WASH OR OTHER
HIGH VOLUME FIXTURE.**



CHRONOMITE
Since 1966

01 ACORN SAFETY®
MODEL NO. S0560
Recessed, Swing Down Eye/Face Wash

02 CHRONOMITE®
MODEL NO. Z-R1818D
Invizible Water Heater R Series
with Disconnect



Click on or tap the product image to access the complete submittal.



POINT OF USE TANKLESS

Model No. CM Series

Chronomite Tankless INSTANT-FLOW CM- ADJ LOW FLOW point-of-use hot water heater (104F to 125F). With Disconnect switch – Check 2095-1 on submittal. Please see link below to specify model needed.

[Submittal Page](#)[Sizing for Non-public Lavatory](#)

POINT OF USE TANKLESS WITH 1070 TMV

Model No. CMI Series

Chronomite Tankless Compliant Mix CMI- LOW FLOW point-of-use hot water heater with integral 1070/1069 Thermostatic mixing valve. With Disconnect switch – Check 2095-1 on submittal. Please see link below to specify model needed.

[Submittal Page](#)[Sizing for Non-public Lavatory](#)

LARGE CAPACITY TANKLESS - SINGLE PHASE

Model No. R-L Series

Chronomite R Series Low Flow Chronomite R-L Series Mighty-Mite - Low Activation models are manufactured to provide reliable point-of-use hot water with flow rate from 0.35 GPM to 5.0 GPM (1.3 LPM to 18.9 LPM). There is no pressure and temperature relief valve needed. With disconnect switch - Check 2095-4 on submittal

With Mop Sink Application Check off A-810VR-1.5 on submittal

[Submittal Page](#)[Sizing for \(3Lavs\) Multiple Lavatories](#)[Sizing for Kitchen sink & Dishwasher](#)[Sizing for Eye/Face wash](#)[Sizing for Mop Sink](#)

LARGE CAPACITY TANKLESS - THREE PHASE

Model No. ER Series

ER_3P Low activation model heaters ER Series With Disconnect switch - Check 2095-4 on submittal With Mop Sink Application Check off A-810VR-2.0 on submittal

[Submittal Page](#)[Sizing for Eye/Face wash](#)[Sizing for Mop Sink](#)

LARGE CAPACITY TANKLESS - THREE PHASE EMERGENCY SHOWERS/TEPID WATER UP TO 30GPM

Model No. ERB Series

Chronomite - Boxer - 3 Phase - Low Activation - L9 models are manufactured to provide reliable tepid water with flow rates from 2.6 gpm to 30.0 gpm. There is no pressure and temperature relief valve needed With disconnect switch – Check U on submittal

[Submittal Page](#)[Sizing for Safety Shower with eyewash](#)

THE INVIZIBLE® WATER HEATER

Model No. Z Series

Many Chronomite heaters can be specified as Invizible heaters. The Invizible option is a code-compliant, concealed electric tankless solution. The vandal-resistant panel keeps your Chronomite protected and functional. The easy-access panel blends into the wall and offers labor savings with an optional prewired disconnect switch. ADA compliant. Select models available with integral ASSE1070 and 1069 compliant thermostatic mixing valve.

[Submittal Page](#)[Sizing for Safety Shower with eyewash](#)