

Model SV16 Accessories

-CSH-WSB CONICAL SHOWERHEAD



Ligature Resistant WaterSense Flanged Showerhead

Ligature and Vandal Resistant Flanged Showerhead with a conical shape. Includes a Removable Vandal Resistant Stainless Steel Non-Aerated Multi-Stream Spray Nozzle fitted with a 1.5 GPM (5.7 LPM) Flow Regulator. Conical Body and Spray Insert are machined from solid type 303 stainless steel and polished to a mirror finish. The conical shape of the Showerhead provides a 30° degree spray angle and prevents it from being used as a ligature point. This Showerhead is IAPMO cUPC certified per ASME A112.18.1 / CSA B125.1 standard for USA & Canada and is EPA certified under WaterSense requirements.

The CSH-WSB Flanged Showerhead is intended for Wall Mounting and includes a 1/2" NPT x O-Ring Adapter, Inlet Connection. Also included is an 8 gage Galvanized Steel Anchor Plate to mount to the finished wall in preparation for mounting the Flanged Showerhead assembly.



ACCESSORIES



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MGI ConTrols® assumes no responsibility for use of void or superseded data. MGI ConTrols®, Lake Bluff, IL, a member of Morris Group International®. Please visit www.mgicontrols.com for most current specifications.

Submittal # **-CSH-WSB**
Rev: 08/15/2024



MGI ConTrols®
42 Sherwood Terrace, Suite #5
Lake Bluff, IL 60044
Phone: (847) 604-4773

www.mgicontrols.com