

Your COMPLETE TRENCH Source!



6" Wide Zip Trench™ 9940 Series

POLYPROPYLENE 6" ZIP TRENCH™ DRAIN SYSTEM

- Fast, long, pre-assembled runs shipped from factory: 9'-10" (3 meter) long channels
- 16 Channels - 12 sloping channels and 4 neutral channels from a depth of 4.81" to 13.81"
- Lighter weight and faster to install than polymer concrete
- Excellent Chemical Resistance
- Temperature rating of 180 degrees vs 140 degrees F with polyethylene
- Load Class A-E
- Built-in slope .6%

POLYPROPYLENE 12" ZIP TRENCH™ DRAIN SYSTEM

- Fast, long, pre-assembled runs: 9'-10" (3 meter) long channels
- 16 channels—12 sloping and 4 neutral from a depth of 7-9/16" - 22-9/16"
- Excellent Chemical Resistance
- Temperature rating of 180 degrees vs 140 degrees F with polyethylene
- Built-in slope 1.07%
- 4 grate types:
 - Class C—Stainless steel perforated and mesh
 - Galvanized steel perforated and mesh
 - Class E—Ductile Iron ADA
 - Ductile Iron Slotted



12" Wide Zip Trench™ 9960 Series

POLYPROPYLENE 6" ENVIRO-FLO® II TRENCH DRAIN SYSTEM



Enviro-Flo® II 9930 Series

- Lightweight, interlocking polypropylene channels are ideal for heavy duty applications
- Excellent Chemical Resistance
- Superior UV resistance
- Bottom outlet on every section
- Temperature rating up to 180° F
- Load Class A - C
- For Extra Heavy Duty applications use the 9940 or 9931



9895 Series

POLYMER CONCRETE TRENCH DRAIN SYSTEM

- Varying widths and depths to meet application needs—1m in length.
- Anchor ribs offer security against upward movement or shifting after installation.
- Widths vary from 3.2" to 14" -Lengths from 1/2 meter (19.68") to 1 meter (39.36")
- Integral rails Galvanized, Stainless Steel, Ductile Iron
- Anchor ribs for mechanical lock into the surrounding concrete
- Load Class A - E

STAINLESS STEEL 6" MODULAR TRENCH DRAIN SYSTEM

- All drains constructed from 16 gage, type 304 Stainless Steel, type 316 Stainless Steel is optional.
- Sanitary Food Service, Chemical Resistance, Aesthetics
- Pre-engineered with a .6% built in slope
- 1 meter lengths (39.36") Flanged bolt together ends with gaskets
- Load Class A - E



9660 Series



9667 Series

LINEAR SHOWER DRAIN SYSTEM

- 2" wide barrier free threshold drain for shower stall.
- Vandal-proof ADA compliant perforated or slotted grates.
- Optional flange or clamping collar w/weep holes
- Optional 2" NPT or 2"x 3" bottom outlet connection with model 215/216 floor drain
- Standard lengths 24", 32" 36", 42" 48" 60"
- Custom lengths available

STAINLESS STEEL 6" - 24" THRESHOLD DRAIN™

- Varying widths and depths to meet various GPM requirements
- Heel-proof grate prevents injury
- Customizable to work with all building structure conditions
- Easily removable grating for fast cleaning and maintenance
- Complies with nationwide Building/Fire Codes
- ADA compliant
- 1.75" deep for post tension slabs
- Load Class A



9679 Series