

## GY Series

### MODEL GYE24

WALL MOUNTED LARGE CAPACITY BOTTLE FILLER DESIGN WITH ANGLED DRINKING FOUNTAINS

#### STANDARD FEATURES

- Bottle Filler and Drinking Fountain Adult ADA Compliant (when properly installed)
- Optionally Available with "Hands Free" Controls with Auto-Purge Function to Assure Fresh Water Supply
- Oversize Bottle Filler Opening with Laminar Flow Spout
- Accommodates Extra Large Bottles Up to 7" Dia x 13" Tall
- Resistant to Sunlight, Heat, Moisture and Wear
- 18 Gauge, Type 304 Stn. Steel Drinking Fountain Bowls
- Heavy Gauge, Type 304 Stainless Steel Construction with Corrosion and Scratch Resistant Finish
- Polished Stainless Steel, Anti-Rotation, Non-Squirt Bubbler
- Heavy Duty, Stainless Steel Access Covers
- 1/4" Thick Stainless Steel Mounting Plate
- 100-Mesh Inlet Strainer

#### SUGGESTED SPECIFICATIONS

Wall Mounted Round Bi-Level Bottle Filler with Drinking Fountain shall be Murdock model GYE24. Construction shall be heavy gauge, all stainless steel with 18 gauge type 304 stainless steel fountain bowls. Provide 1/4" thick stainless steel mounting plate to securely anchor unit to wall. Access Panels shall be secured with vandal-resistant stainless steel screws. Drinking Fountain shall be activated by a front mounted self-closing Pushbutton with Cartridge Valve Assembly, using less than 5 pounds of force to activate with an adjustable stream regulator controlling the water flow. Bubblers shall be stainless steel with non-squirt feature and operate on water pressure range of 20-105 PSIG. Extra height Bottle Filler shall be activated a Pneumatic Pushbutton using less than 5 lbs of force to activate and provide 1.5 GPM (5.7 LPM) Laminar Flow Spout. Provide unit with Elbow Waste connection. **P-Trap shall be installer provided behind wall (Optional -PT P-Trap with access below fixture is available).** Unit shall contain a 100-Mesh Inlet Strainer. Unit shall be certified to Public Law 111-380 (NO-LEAD) and NSF/ANSI/CAN 61. Fixture to meet ADA and ADA Reach requirements when mounted appropriately. **Optional -SO with Auto-Purge Sensor function shall activate Bottle Filler for 10 second duration 24 hour after last activation as standard and allow for purge cycle adjustment.**

#### Product Warranty

#### 3000 Gallon PFAS Filter Certifications

Option Notes:

<sup>1</sup>See separate option sheet

Complies with the following standards:



Federal Public Law 111-380 (No Lead)



NSF/ANSI/CAN 61

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA  
Phone 800-453-7465 or 626-333-2543 • [www.murdockmfg.com](http://www.murdockmfg.com)

Member of  
MORRIS GROUP  
INTERNATIONAL



Model: GYE25-R Shown

"FOR INDOOR AND OUTDOOR USE"

#### MODEL:

(Must Specify)

- GYE24 Satin Stainless Finish
- GYE25 Green Powder-Coated
- GYE26 Red Powder-Coated
- GYE27 Blue Powder-Coated (Shown)

Custom color finishes available upon request

#### ADA DRINKING FOUNTAIN ORIENTATION

(Must Specify)

- L ADA Drinking Fountain Left Side (Opposite)
- R ADA Drinking Fountain Right Side (Shown)

#### OPTIONS

(additional costs may be incurred)

- FRA3 Freeze Resistant Valve, Three Valves<sup>1</sup> (N/A w/ Filter<sup>1</sup> & Sensor)
- LOGO Customer specified logo
- SLPT 10° Bottle Filler Sloped Top
- SOC Concealed Sensor Operated Drinking Fountain Battery Operated with Auto-Purge Function to Assure Fresh Water Supply (N/A with -FRA2<sup>1</sup>)
- SO Sensor Operated Bottle Filler, Battery Operated with Auto-Purge Function to Assure Fresh Water Supply (N/A with -FRA2<sup>1</sup>)
- 316 Type 316 Stainless Steel Construction

#### ACCESSORIES

(additional costs may be incurred)

- AP Auto-Purge Sensor Function Controller
- LSR Bowl with Leaf & Debris Strainer<sup>1</sup>
- PT 1-1/4" OD P-Trap (Access Below Fixture) (N/A with -FRA2)
- SK8 Cane Detection Skirt (for Non-ADA Arm)
- TF 120VAC/9V DC Plug-In Transformer
- WF3000 3000-Gallon PFAS Water Filter<sup>1</sup> NSF/ANSI, PFAS, Lead, Bacteria, Chlorine, Microplastics (N/A with -FRA2)

