

KWIK-CON™

IDEAL APPLICATION: Point of Use CM and CMI Models

PRODUCT FEATURES

- Conduit Assembly - Saves time by ease of installation and pre-assembly
- Approved of concealed or exposed installations
- Lightweight Exterior rated for 600-Volt
- Solid copper THHN/THWN insulated single conductors with a green insulated copper grounding conductor
- 8 inch conductor leads with ½ inch insulation stripped
- Color coded conductors
- Easy to connect wire to wire, using supplied wire nuts
- Connect to a standard single gang outlet box using wall plate provided
- Offered in both metallic and non-metallic versions



C12 shown with Heater CM-20L/120

Metallic Assembly:

Rated for 600-Volt

2 foot length type MC cable with factory installed zinc-die cast fittings

Aluminum interlocked armor

Non-Metallic Assembly:

Rated for 600-Volt

2 foot length with factory installed fittings

PA6 UL 94-VO material

Protection Class IP68, IP66

MODEL	TYPE	CM-12L/** CM-15L/** CM-20L/** CMI-12L/** CMI-15L/** CMI-20L/**	CM-30L/** CMI-30L/**	CM-40L/** CMI-40L/**
C8	Metallic			X
C10			X	
C12		X		
C-NM8	Non-Metallic			X
C-NM10			X	
C-NM12		X		

***120, 208, 240 or 277v

**Complies
with
Standards
for:**



CHRONOMITE LABORATORIES, INC.

17451 Hurley St. :: City of Industry, CA 91744

Phone 800-447-4962 :: 626-937-4270

Fax 626-937-4279 :: www.chronomite.com

MEMBER OF

