



Model: WHCHS

Ligature Resistant Handheld Shower & Collapsible Handheld Shower Mounting Bracket

Ligature Resistant Adapter Base with Handheld Shower includes a 60" Flexible Stainless Steel Hose, Expansion Plug Quick-Disconnect, Handheld Shower and a Collapsible Handheld Shower Mounting Bracket. Wall Mounting Brackets are heavy gauge type 304 stainless steel with white powder coat finish. Used for ADA applications where a Handheld Shower is required. The Handheld Shower can be used as needed but when removed from Shower area, the Adapter Base and Collapsible Shower Mounting Bracket are Ligature Resistant.

Handheld Shower Mounting Bracket includes an Auto-release hook with an adjustable release range of 0 to 25 lbs. The release point is factory set to release at 10 lbs. +/- 2 lbs. at the base of the hook.

Post Adjustment of release force is through Post End using a Wrench for #10-32 Allen Recess Set Screw.

For maximum ligature resistance: A fixed Conical Shower Head is recommended. (Verify local requirements to ensure ADA compliance.)

IMPORTANT: This item is not sold as a "break away Hose." The WHCHS is a Quick-Disconnect design (only), used for removal of the Handheld Shower however, without a ligature point remaining on the Socket end after removal.

FEATURES:

- Ligature Resistant Adapter Base
- Expansion Plug Quick-Disconnect with a Vacuum Breaker
- 1.5 GPM Handheld Shower with Pushbutton Non-Positive Shut-Off
- 60" Stainless Steel Flexible Hose
- Collapsible Handheld Shower Mounting Bracket with Adjustable Release Range Using Set Screw
- Vandal Resistant Construction
- 1/2" NPT Supply Connection
- Solid Lead-Free Brass & Stn Stl Construction
- ADA / CBC (California Building Code) 1115B.4.4.5 Compliant when Mounted at a Maximum of 48" Above Floor
- Front Mounted with 1/4"-20 x 1-1/4" Long UNC Tamper resistant screws for use with Wall Anchors provided by others.
- **Note:** Screws provided have Machine Screw Thread and may not be suitable for all Wall types. When required, Installer shall provide alternate Screw type and Wall Anchors to suit Wall construction.



IMPORTANT: Quick Disconnect Device has no positive shut-off. Water will flow from Conical Nozzle without restriction when Hose and Hand Held assembly is removed.

Please visit www.whitehallmfg.com for most current specifications.



Complies with the following standards:



Federal Public Law 111-380 (No Lead)

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

